

U-POL™

SAFETY DATA SHEET

UPOL BODYFILLER RANGE

Page 1

Issued: 20/04/2004

Revision No: 5

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UPOL BODYFILLER RANGE

Product code: VARIOUS

Synonyms: P38, P40, FIBRAL, QUICSAND, DOLPHIN, EASY, MONARCH
DOLPHIN, EASY, EASYLITE, EXTRA, EXTRA GOLD, FANTASTIC, FIBRAL, GALVX,
HOTSHOT, LUCKY7, MONARCH, QUICSAND, TOPSTOP, TOPSTOP GOLD,
UPOLB, UPOLC, UPOLD, UPOLE,

Use / description of product: POLYESTER REPAIR PASTE CONTAINING STYRENE

Company name: U-Pol Products
Denington Industrial Estate
Denington Road
Wellingborough
Northants
NN8 2QP
United Kingdom
Tel: 44-(0)-1933 230300
Fax: 44-(0)-1933 230351
Emergency tel: 44-(0)-1933 230310

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: STYRENE 10-30%
EINECS: 202-851-5 CAS: 100-42-5
[-] R10; [Xn] R20; [Xi] R36/38

3. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation. Irritating to eyes and skin.

Other hazards: Flammable. Harmful by inhalation. Irritating to eyes. Irritating to skin.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Wash immediately with plenty of soap and water.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Wash out mouth with water. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.
- Exposure hazards:** Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.
- Protection of fire-fighters:** Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand.

7. HANDLING AND STORAGE

- Handling requirements:** Ensure there is sufficient ventilation of the area.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Hazardous ingredients:** STYRENE
TWA (8 hr exposure limit): 430 mg/m³ STEL (15 min exposure limit): 1080 mg/m³ (MEL)
- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Respiratory protective device with particle filter.
- Hand protection:** Nitrile gloves.
- Eye protection:** Safety glasses with side-shields.
- Skin protection:** Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Paste
- Odour:** Aromatic
- Evaporation rate:** Slow
- Solubility in water:** Insoluble
- Also soluble in:** Most organic solvents.
- Viscosity:** Highly viscous
- Viscosity value:** 500,000 CP
- Flammability limits %: lower:** 1.1
- upper:** 6.1
- Flash point°C:** 32

Autoflammability°C: 490
Relative density: 1.5
VOC g/l: 300

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Direct sunlight. Heat. Sources of ignition.
Materials to avoid: Oxidising agents.
Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: STYRENE
 IVN MUS LD50 90 mg/kg
 ORL MUS LD50 316 mg/kg
 ORL RAT LD50 2650 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water. Heavier than water.
Persistence and degradability: Not biodegradable.
Bioaccumulative potential: No data available.
Other adverse effects: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D1 Tipping above or underground (e.g. landfill, etc.).
Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 3269	ADR Class: 3
Packing group: III	Classification code: F1
Shipping name: POLYESTER RESIN KIT	
Labelling: 3	



IMDG / IMO

UN no: 3269	Class: 3
Packing group: III	EmS: F-E,S-D

Marine pollutant: .

Labelling: 3

IATA / ICAO

UN no: 3269

Class: 3

Packing group: III

Packing instructions: 312

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R20: Harmful by inhalation.
R36/38: Irritating to eyes and skin.

Safety phrases: S2: Keep out of the reach of children.
S3: Keep in a cool place.
S46: If swallowed, seek medical advice immediately and show this container or label.
S51: Use only in well-ventilated areas.

VbF: All

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R10: Flammable.
R20: Harmful by inhalation.
R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.